

## THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A power management system for supplying power to an output circuit  
5 comprising:  
a plurality of rechargeable batteries;  
first conversion means for converting a supply voltage to a battery voltage to  
enable charging of one or more of the rechargeable batteries; and  
switch means to enable a selected battery of the plurality of rechargeable  
10 batteries to be connected to an output circuit to enable the selected battery to be  
discharged through the output circuit.
2. A system according to claim 1 wherein the switch means is connected to the  
first conversion means to enable charging to the selected battery.  
15
3. A system according to claim 1 or claim 2 further comprising second conversion  
means connected between the output circuit and the switch means for converting the  
voltage of the selected battery to a voltage for use by the output circuit thereby  
discharging the selected battery.  
20
4. A system according to any one of the previous claims wherein a rechargeable  
battery of the plurality of rechargeable batteries is chosen, one at a time, in order to be  
charged or discharged.
- 25 5. A system according to any one of the previous claims wherein the first  
conversion means acts as the second conversion means.
6. A system according to any one of the previous claims wherein the switch means  
comprises a plurality of switches enabling connection of a respective rechargeable  
30 battery of the plurality of rechargeable batteries to the first conversion means and to the  
output circuit.

7. A system according to any one of the previous claims further comprising a control unit for controlling the switch means to either enable charging or discharging of a rechargeable battery of the plurality of rechargeable batteries.
- 5 8. A system according to claim 7 further comprising multiplexer means having an input connected to one terminal of each rechargeable battery in the plurality of rechargeable batteries to enable the voltage signals pertaining to each battery to be selected and forwarded to an analogue to digital converter.
- 10 9. A system according to claim 8 further comprising a shunt impedance means connected to the other terminal of each battery in the plurality of rechargeable batteries to measure the charge current of each battery, represented as a voltage drop across the shunt impedance means.
- 15 10. A system according to claim 9 wherein the shunt impedance means is connected in parallel to a shunt switch to short circuit the shunt impedance means when the shunt impedance is not in use.
11. A system according to claim 10 further comprising amplification means  
20 connected between the shunt impedance means and the multiplexer means to amplify the voltage drop across the shunt impedance means to the input voltage range of the analogue to digital converter.
12. A system according to claim 11 wherein the analogue to digital converter  
25 measures individual battery voltage of any one of the rechargeable batteries in the plurality of rechargeable batteries and converts the measured voltage to a digital value.
13. A system according to claim 11 or claim 12 wherein the analogue to digital  
converter measures the voltage drop across the shunt impedance means and converts  
30 the measured voltage into a digital value.
14. A system according to claim 13 further comprising a register for storing information pertaining to each battery.

15. A system according to claim 14 wherein said information comprises any one or more of charge status of each battery in the plurality of rechargeable batteries , error status of each battery in the plurality of rechargeable batteries or a flag identifying whether a battery in the plurality of rechargeable batteries has been disabled from  
5 being charged or discharged.

16. A system according to claim 15 wherein the control unit is in communication with the register and with the analogue to digital converter for processing signals and data from the analogue to digital converter and from the register.

10

17. A system according to claim 16 wherein the control unit periodically senses the presence of a voltage at the input to the switch means.

18. A system according to claim 17 wherein the control unit selects a battery of the  
15 plurality of rechargeable batteries to be charged or discharged on the basis of information stored in the register pertaining to a particular battery of the plurality of rechargeable batteries.

19. A system according to any one of the previous claims wherein the second  
20 conversion means enables discharging of a battery of the plurality of rechargeable batteries such that charge in the selected battery of the plurality of rechargeable batteries is forwarded to the output circuit.

20. A system according to claim 19 wherein the output circuit forms part of an  
25 implantable device.

21. A system according to claim 20 wherein the implantable device is an implantable hearing prosthesis.

30 22. A system according to any one of the previous claims wherein the first conversion means includes an inductive means, one or more switches and a switch control unit to enable charging and/or discharging of a selected battery of the plurality of rechargeable batteries.

23. A system according to any one of the previous claims wherein the second conversion means includes an inductive means, one or more switches and a switch control unit to enable discharging of a selected battery of the plurality of rechargeable batteries.

5

24. A system according to any one of the previous claims wherein the supply voltage is derived from an inductive means and rectified into a direct voltage to be applied to the inductive means of the first conversion means.

10 25. A method of managing the supply of power to an output circuit in a system that includes a plurality of rechargeable batteries, the method comprising the steps of:

converting a supply voltage to a battery voltage to enable charging of one or more of the plurality of the rechargeable batteries; and

15 connecting a battery in the plurality of rechargeable batteries, using switch means, to the output circuit to enable the connected battery to be discharged through the output circuit.

26. A method according to claim 25 wherein the connected battery in the plurality of rechargeable batteries is discharged to the output circuit by converting the voltage  
20 output from the connected battery in the plurality of rechargeable batteries to a voltage for use by the output circuit.

27. A method according to claim 25 or claim 26 further comprising the step of providing the switch means in the form of a bank of switches, one for each  
25 rechargeable battery of the plurality of rechargeable batteries.

28. A method according to claim 27 further comprising the step of controlling the switch means to enable the charging or discharging of a selected battery of the plurality of rechargeable batteries on the basis of information stored in a register on each of the  
30 rechargeable batteries in the plurality of rechargeable batteries.

29. A method according to claim 28 further comprising the steps of multiplexing and measuring parameters, such as battery voltage, battery charge and battery current,

pertaining to each rechargeable battery in the plurality of rechargeable batteries for storage as digital values in the register.

30. A method according to claim 29 further comprising the step of maintaining a  
5 record in the register on the state of charge of each rechargeable battery in the plurality of rechargeable batteries.

31. A method according to claim 30 further comprising the step of providing an optimum range, as a percentage value of the state of charge, within which each  
10 rechargeable battery in the plurality of rechargeable batteries is charged and/or discharged.

32. A method according to claim 31 further comprising the step of disabling charging of a battery of the plurality of rechargeable batteries where the charge of that  
15 battery of the plurality of rechargeable batteries is above a first percentage limit of the state of charge.

33. A method according to claim 31 or claim 32 further comprising the step of terminating the discharging of a battery of the plurality of rechargeable batteries where  
20 the charge of that battery of the plurality of rechargeable batteries is below a second percentage limit of the state of charge.